

PVC Strip Connectors

A strip of 12 transparent flexible polyurethane connectors with brass inserts and chrome plated steel terminal screws.

- Maximum continuous operating temperature: 80°C
- Supplied in shrink wrapped packs

Ref	240V Rating	Clamp Area	Hole Dia.	Pack Qty
2A	2A	4mm ²	2.8mm	20
5A	5A	6mm ²	3.6mm	20
15A	15A	10mm ²	4.2mm	20
30A	30A	16mm ²	5.5mm	10
60A	60A	25mm ²	7.9mm	10



Certified Strip Connector

A strip of 12 white easy snap European CE branded quality connectors with brass inserts and chrome plated steel terminal screws.

- Maximum continuous operating temperature: 80°C
- Supplied in shrink wrapped packs
- Screws terminals come already opened

Ref	240V Rating	Clamp Area	Hole Dia.	Pack Qty
2ACE	2A	4mm ²	2.8mm	10
5ACE	5A	6mm ²	3.6mm	10
15ACE	15A	10mm ²	4.2mm	10
30ACE	30A	16mm ²	5.5mm	10
60ACE	60A	25mm ²	7.9mm	10



F4P Coloured Heat Shrink Pack

Suitable for electrical insulation and bonding of cables and connectors, as well as corrosion proofing metallic rods, tubes and aerials.

- Minimum 2:1 shrink ratio
- Colours included: black, blue, brown, grey, green/yellow
- Shrink temperature: 90°C
- Continuous operation temperature: -55°C to +125°C
- Flame retardant - UL VW-1, F-mark
- Resistant to common fluids and solvents
- Approved to UL 224 VW-1

Ref	Size
F4PHSP4824	4.8 - 2.4mm
F4PHSP10050	10.0 - 5.0mm
F4PHSP7030	7.0 - 3.0mm
F4PHSP190100	19.0 - 10.0mm

